



SPECIFICATIONS MODEL 1218FT

APPROVED UNDER
DHS AEL# 030E-03-CACS
for purchase under certain
FEMA PREPAREDNESS GRANTS
(CALL FOR DETAILS)
CCR



FEATURES

- 1 - Model 1218FT Inflatable Plug with single 2" flow through port
- 1 - 2" brass ball valve
- 1 - 90 degree ELL with extension tubes
- 1 - two piece air hose for inflation and deflation
- 1 - Grounding cable with clamps
- 1 - 25ft 1/2" air hose with couplers
- 1 - Nitrile rubber sleeve
- Preset vent valve, to prevent over inflation
- Fixed mounted quick connect for air inflation and deflation
- Transparent front and rear flanges to allow for sight inspection (for viewing fluid levels)
- Unit is constructed with a Thermo PolyUrethane which is impervious to hydrocarbons and 99% of known chemicals
- Lightweight and compact for easy storage and transport
- 1 - Pelican 1630 case, waterproof and weather resistant
- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel padlock protectors
- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings

SPECIFICATIONS

Model 1218FT Transport Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)
31.28" x 24.21" x 17.48" (79.4 x 61.5 x 44.4 cm)	27.70" x 20.98" x 15.50" (70.3 x 53.3 x 39.4 cm)

*This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.

Lid Depth	Bottom Depth	Total Depth
3.25" (8.3 cm)	12.14" (30.8 cm)	15.50" (39.4 cm)

Weight with foam	Weight without foam	Buoyancy Max.
36 lbs. (16.33 kg)	31 lbs. (14.06 kg)	350 lbs. (158.76 kg)

Range Temperature	No. of Wheels
-40 / 210° F (-40 / 99° C)	4