



# SPECIFICATIONS MODEL 2436FT

APPROVED UNDER  
DHS AEL# 030E-03-CACS  
for purchase under certain  
FEMA PREPAREDNESS GRANTS  
(CALL FOR DETAILS)  
CCR



## FEATURES

- 1 - Model 2436FT Inflatable Plug with dual 2" flow through ports
- 2 - 2" brass ball valves
- 1 - 90 degree ELL with extension tubes
- 1 - two piece air hose for inflation and deflation
- 1 - Grounding cable with clamps
- 1 - Plastic Strainer for upper rear port intake
- 1 - 25ft 1/2" air hose with couplers
- 1 - Nitrile rubber sleeve
- Preset vent valve, to prevent over inflation
- Fixed mounted quick connect for air inflation and deflation
- Transparent front and rear flanges to allow for sight inspection (for viewing fluid levels)
- Unit is constructed with a Thermo PolyUrethane which is impervious to hydrocarbons and 99% of known chemicals
- Lightweight and compact for easy storage and transport
- 1 - Pelican 1780 case with 50/50 lid-to-base ratio for easy loading, completely detachable lid for full access
- Watertight, weather resistant, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel padlock protectors
- 4 strong polyurethane wheels with stainless steel bearings

## SPECIFICATIONS

### Model 2436FT Transport Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
44.90"	25.32"	42.00"	22.00"
(114 x 64.3 x 41.9 cm)		(106.6 x 55.9 x 38.3 cm)	

Lid Depth	Bottom Depth	Total Depth
7.58"	7.30"	14.88"
(19.2 cm)	(18.5 cm)	(37.8 cm)

Weight with foam	Weight without foam	Buoyancy Max.
49 lbs.	38.4 lbs.	500 lbs.
(22.23 kg)	(17.42 kg)	(226.8 kg)

Range Temperature	No. of Wheels
-40 / 210° F	4
(-40 / 99° C)	