



APPROVED UNDER  
**DHS AEL# 030E-03-CACS**  
 for purchase under certain  
**FEMA PREPAREDNESS GRANTS**  
 (CALL FOR DETAILS)  
 CCR


**U.S. DOT EMERGENCY RESPONSE SET**  
**MODELS 1218FT, 2436FT, 1218S, 2436S**

***FLOWSTOP the world's only true Hazmat pipe plug with/without flow through ports.***



**FEATURES 1218FT, 2436FT / 1218S, 2436S**

- 2) Flow Through Inflatable drain line plugs servicing 12" - 18" & 24" - 36" Pipes
- 2) Stopper plugs for 12" - 18" & 24" - 36" drain line pipes
- Imperivous to hydrocarbons and 99% of known chemicals
- Light weight for Quick Deployment
- Low Pressure inflatables
- Low maintenance
- Storage cases and all components included
- Pipe must be free of all debris, sediment and foreign material to insure a complete seal to pipe wall
- FEMA SEL# 030E-03-CACS



1218FT



2436FT



1218S



2436S

## FEATURES 1218FT



1218FT

- 1- Model 1218FT Inflatable Plug with single 2" flow through port
- 1- 2" brass ball valve
- 1- 90 degree ELL with extension tubes
- 1- two piece air hose for inflation and deflation
- 1- Grounding cable with clamps
- 1- 25ft 1/2" air hose with couplers
- Fixed mounted quick connect for air inflation and deflation
- Transparent front and rear flanges to allow for sight inspection (for viewing fluid levels)
- Unit is constructed with a Thermo PolyUrethane which is impervious to hydrocarbons and 99% of known chemicals
- 1- Nitrile rubber sleeve
- 1- Nitrile rubber sleeve
- Preset vent valve, to prevent over inflation
- Fixed mounted quick connect for air inflation and deflation
- Transparent front and rear flanges to allow for sight inspection (for viewing fluid levels)
- Unit is constructed with a Thermo PolyUrethane which is impervious to hydrocarbons and 99% of known chemicals
- 1- Nitrile rubber sleeve
- Fixed mounted quick connect for air inflation and deflation
- Transparent front and rear flanges to allow for sight inspection (for viewing fluid levels)
- Unit is constructed with a Thermo PolyUrethane which is impervious to hydrocarbons and 99% of known chemicals
- Lightweight and compact for easy storage and transport
- 1- Pelican 1630 case which is waterproof and weather resistant
- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel padlock protectors
- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings

## FEATURES 2436FT



2436FT

- 1- Model 2436FT Inflatable Plug with dual 2" flow through ports
- 2- 2" brass ball valves
- 1- 90 degree ELL with extension tubes
- 1- two piece air hose for inflation and deflation
- 1- Grounding cable with clamps
- 1- Plastic Strainer for upper rear port intake
- Unit is constructed with a Thermo PolyUrethane which is impervious to hydrocarbons and 99% of known chemicals
- Lightweight and compact for easy storage and transport
- 1- Pelican 1780 case with 50/50 lid-to-base ratio for easy loading, completely detachable lid for full access
- Watertight, weather resistant, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel padlock protectors
- Fold down handles
- 4 strong polyurethane wheels with stainless steel bearings
- 1- 25ft 1/2" air hose with couplers
- 1- Nitrile rubber sleeve
- Preset vent valve, to prevent over inflation
- Fixed mounted quick connect for air inflation and deflation
- Transparent front and rear flanges to allow for sight inspection (for viewing fluid levels)

## FEATURES 1218S



1218S

- 1- Model 1218S Inflatable Stopper Plug
- 1- two piece air hose for inflation and deflation
- 1- 25ft 1/2" air hose with couplers
- 1- Nitrile rubber sleeve
- Preset vent valve, to prevent over inflation
- Fixed mounted quick connect for air inflation and deflation
- Transparent front and rear flanges to allow for sight inspection (for viewing fluid levels)
- Tether line standard with each S model plug
- Unit is constructed with a Thermo PolyUrethane which is impervious to hydrocarbons and 99% of known chemicals
- 1- Pelican 1630 case which is waterproof and weather resistant. Pelican case is optional when ordering a single plug. Optional installation tool (IT3/6) available. Call for prices and information.

## FEATURES 2436S



2436S

- 1- Model 2436S Inflatable Stopper Plug
- 1- two piece air hose for inflation and deflation
- 1- 25ft 1/2" air hose with couplers
- 1- Nitrile rubber sleeve
- Preset vent valve, to prevent over inflation
- Fixed mounted quick connect for air inflation and deflation
- Transparent front and rear flanges to allow for sight inspection (for viewing fluid levels)
- Tether line standard with each S model plug
- Unit is constructed with a Thermo PolyUrethane which is impervious to hydrocarbons and 99% of known chemicals
- 1- Pelican 1630 case which is waterproof and weather resistant. Pelican case is optional when ordering a single plug. Optional installation tool (IT3/6) available. Call for prices and information