



**ELLIPTICAL  
PIPE PLUGS  
MODELS E1930FT,  
E2945FT**

APPROVED UNDER  
DHS AEL# 030E-03-CACS  
for purchase under certain  
FEMA PREPAREDNESS GRANTS  
(CALL FOR DETAILS)  
CCR

Flowstop offers Elliptical inflatable plugs that are stoppers or flow throughs:  
Flowstop Model E1930FT is a single 2" Flow Through or Stopper Model.  
Flowstop Model E2945FT is a dual 2" Flow Through or Stopper Model.  
Call for details and pricing. We also design and develop custom pipe plugs, call with your specs.

**FLOWSTOP the world's only true Hazmat pipe plugs with/without flow through ports.**



E2945FT

**FEATURES E1930FT & E2945FT**

**E2945FT Dual Port Model**

- 1- 90 degree ELL available in aluminum or polypropylene \*\* with extension tubes
- 2 - 2" (option) brass or polypropylene \*\* ball valves
- 1 plastic strainer for upper rear port intake
- 1- 10ft. grounding cable with clamps and grounding peg on face plate
- 2 piece air hose    • 25' 1/2" air hose w/couplers
- 1780 Pelican case

\*\* Same as regular dual ports however, no nitrile sleeve \*\*

\*\* Recommended

FlowStop features elliptical pipe plugs in 2 sizes, offered as Stopper or Flow Through models. Current sizes service: 19" rise, with 30" span available as a single 2" Flow Through port or Stopper plug. The 29" rise with 45" span is available as a 2" dual port Flow Through or Stopper plug.

**E1930FT Single Port Model**

- 1- 90 degree ELL available in aluminum or polypropylene \*\* with extension tubes

- 2 - 2" (option) brass or polypropylene \*\* ball valves
- 1- 10ft. grounding cable with clamps and grounding peg on face plate
- Extension pipe for elbow
- Pre-set vent valve
- 1780 Pelican Case
- 25' 1/2" air hose with couplers

\*\* Can be ordered solid black or with transparent front and rear flanges \*\*

\*\* Recommended

**Each E Stopper Model comes with:**

- 1-25' 1/2" air hose with couplers
  - 1-25' 1/2" tether rope for retrieval
  - 1-2 piece air hose for inflation & deflation
- Elliptical Stoppers are equipped with aluminum plates, front and rear of plug, with front plate equipped with welded D Ring.

\*\* Storage & carry cases are OPTIONAL \*\*